@LUMIPARTS @LUMIPARTSLIGHTING () in () |





Lucio delivers a sophisticated lighting experience with its innovative dip switch technology, allowing for complete customization to suit individual preferences. It offers multiple light output settings and three color temperatures (3000K, 3500K, 4000K), enabling effortless creation of the desired ambiance. The luminaire series' power options are meticulously tailored to various lengths, ensuring optimal lighting levels at all times. Renowned for its exceptional flexibility, Lucio is designed with versatility and adaptability at its core. Equipped with standard DALI-2 dimming capabilities, it provides the choice between direct and indirect lighting.

Save on energy and costs!

With a system efficiency up to 121 lumens per watt.



Dali 2 Dimmable as Standard

Dipswitch

A special dipswitch for 3000K, 3500K, or 4000K and various power options with different light outputs.


Versatile solution with upward illumination or cover plate


With the standard supplied coverplate and the option to easily upgrade to an uplight, the Lucio effortlessly adapts to evolving needs. Whether you prefer direct lighting or wish to create an indirect, ambient glow on the ceiling, the Lucio offers the flexibility to meet your preferences.

Lucio's Highlights



Available with uplight





Combine several Lucios into a single entity with the 15-meter diffuser roll.

Do you have inquiries or seek further information about our Lucio?

Scan the QR code for all dates, inquiries, or to get in touch with us!



Nijverheidsweg 2 | 2421 LR Nieuwkoop T +31(0)172 574 500 | info@lumiparts.nl www.lumiparts.nl

LUCIO PRODUCT HIGHLIGHTS

DALI 2 DIMMABLE AS STANDARD

COVER PLATE OR UPLIGHT OPTION -

The Lucio comes with a standard blind plate included in the fixture. You have the flexibility to switch this out with the uplight with just one click. The uplight offers indirect lighting at the top of the fixture and is also offered in black for all sizes. The light from the Lucio will be dispersed using the uplight option, with 70% of the light output at the bottom and 30% from the uplight. The uplight's light color matches the direct light.

CONNECT MULTIPLE LUCIO'S

Interconnect various Lucio fixtures using our unique connection components to achieve a cohesive design. Enhance your design by incorporating a 15-meter roll of opal finish.



DIPSWITCH

COLOURS

A unique dip switch is located on the top of the fixture, providing the ability to adjust light colors to 3000K, 3500K, and 4000K. The light output is adjustable through the driver.



Accessories

Establish a uniform design by linking the various Lucios. A 15-meter roll of shielding is specifically designed for the Lucio, and we utilize special connectors to offer you full flexibility in your lighting design.

Suspension Set Black 2 meter

Suspension Set White 2 meter

Surface mounted set

Straight connection 1 piece

Lucio opal diffuser rol opal Rol 15000mm





