




Ardea V2

Track light with dipswitch



Features:

- Architectural design with flush in-track driver
- Dip switch for CCT & Lumen Output
- High color rendering CRI >90
- High performance lenses with comfortable light

System Power	40W			49W			59W			68W		
CRI - MCE	CRI > 90 _ McAddams Elipse 3											
CCT	3000K	3500K	4000K	3000K	3500K	4000K	3000K	3500K	4000K	3000K	3500K	4000K
System Lumen	5550lm	5900lm	5800lm	6400lm	7000lm	6800lm	7500lm	8100lm	7850lm	8200lm	9150lm	8700lm
System Efficacy	137lm/w	151lm/w	144lm/w	130lm/w	148lm/w	139lm/w	127lm/w	144lm/w	133lm/w	121lm/w	141lm/w	128lm/w
L+B Values	50.000 hrs L80+B10											
Circuit breaker info	B16 = 23 B20 = 29 C16 = 30 C20 = 38											
Beamspread	90° Standard - Optional on request: 30°,60°, asymetrical & Double asymetrical											

PRODUCT LIST						
Ardea V2 CRI90 90° incl. driver with output selectable dipswitch						
Article No.	Product Name	Color	CCT	CRI	Size	Weight
2.17.4972	Ardea V2 930/935/940 90° Dipswitch White	White	3000/3500/4000K	>90	1504x 64mm	1,7 kg
2.17.4977	Ardea V2 930/935/940 90° Dipswitch Black	Black	3000/3500/4000K	>90	1504x 64mm	1,7 kg



Low glare lenses



Dip Switch CCT

1	2	3	mA	Watt
Off	Off	Off	250mA	40
On	Off	Off	300mA	49
On	On	Off	350mA	59
On	On	On	400mA	68

Dip Switch Lumen Output

Light distribution

