

Light efficiency:

**118 Lumen/Watt**

Light quality:

**CRI: 94,0**

Color temperature:


**2950 K**

**Output: 4058 lm**

**Peak: 1918 cd**

**Power: 34,4 W**

**PF: 0,96**



Tracking number: [n/a](#)

Product name:

**Plata CCT Dipswitch 620x620 3000k 35W**

Item number:


Date and time:

**31-5-2023 09:11:29**

Description:

**PL-6262BL-H-365**

**3.10.0538 Driver 900mA**




Beam angle

**86,7°**






CIE 1931  
x: 0,442  
y: 0,407

Spectra




Power






**TM-30: 91,6**



**CRI: 94,0 (R1-R8)**



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95,6	95,8	95,1	95,8	95,1	96,3	93,3	84,8	62,4	89,1	95,7	84,2	95,5	96,0	90,4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91,3	93,6	89,9	92,8	93,7	91,8	92,2	94,7	96,0	94,4	91,1	88,3	89,0	87,1	91,6	85,1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
87,0	94,9	89,5	92,4	92,6	89,7	90,6	94,3	97,5	93,9	94,9	95,1	95,0	88,2	87,1

**CQS: 91,4**



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2950 K	94,0	62,4	91,6	101,5	91,4	0,442	0,407	0,252	0,349	0,0007







**Rf 91,6**


Fidelity index Rf

**Rg 101,5**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	91	-5%	-1%
2	94	-3%	2%
3	90	-1%	5%
4	93	1%	3%
5	94	3%	4%
6	92	5%	1%
7	92	2%	-4%
8	95	2%	-2%
9	96	-1%	-1%
10	94	-2%	2%
11	91	0%	6%
12	88	5%	0%
13	89	4%	-7%
14	87	4%	-9%
15	92	0%	-5%
16	85	-2%	-12%





**Beam intensities from 1-20m**

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
1918lx	479lx	213lx	120lx	77lx	53lx	39lx	30lx	24lx	19lx	16lx	13lx	11lx	10lx	9lx	7lx	7lx	6lx	5lx	5lx
178,1fc	44,5fcd	19,8fcd	11,1fcd	7,1fcd	4,9fcd	3,6fcd	2,8fcd	2,2fcd	1,8fcd	1,5fcd	1,2fcd	1,1fcd	0,9fcd	0,8fcd	0,7fcd	0,6fcd	0,5fcd	0,5fcd	0,4fcd

**Intensities in 0° c-plane**

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
1918	1907	1878	1835	1775	1698	1595	1427	1151	876	677	500	358	272	213	162	117	68	18	6
100%	99%	98%	96%	93%	89%	83%	74%	60%	46%	35%	26%	19%	14%	11%	8%	6%	4%	1%	0%

**Intensities in 90° c-plane**

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
1918	1907	1878	1835	1775	1698	1595	1427	1151	876	677	500	358	272	213	162	117	68	18	6
100%	99%	98%	96%	93%	89%	83%	74%	60%	46%	35%	26%	19%	14%	11%	8%	6%	4%	1%	0%

**Intensities in 180° c-plane**


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
1918	1907	1878	1835	1775	1698	1595	1427	1151	876	677	500	358	272	213	162	117	68	18	6
100%	99%	98%	96%	93%	89%	83%	74%	60%	46%	35%	26%	19%	14%	11%	8%	6%	4%	1%	0%

**Intensities in 270° c-plane**

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
1918	1907	1878	1835	1775	1698	1595	1427	1151	876	677	500	358	272	213	162	117	68	18	6
100%	99%	98%	96%	93%	89%	83%	74%	60%	46%	35%	26%	19%	14%	11%	8%	6%	4%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
86,7°	143,9°	173,6°	86,1%	67,3%

**iso-candela diagram**




10%	192 cd
20%	384 cd
30%	575 cd
40%	767 cd
50%	959 cd
60%	1151 cd
70%	1342 cd
80%	1534 cd
90%	1726 cd

Conditions:

Number of c-planes: 8

Candela at center: 1918 cd

**iso-lux diagram**



3%	0,575 lx
5%	0,959 lx
10%	1,92 lx
30%	5,75 lx
50%	9,59 lx

Conditions:

Number of c-planes: 8

Lux at center: 19,2 lx

*Lux distribution on a surface  
when lamp is mounted at 10  
meters from the surface.*

**Glare evaluation according to UGR**


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	15,5	16,5	15,7	16,8	17,0	15,5	16,5	15,7	16,8	17,0
	3H	16,3	17,3	16,7	17,6	17,8	16,3	17,3	16,7	17,6	17,8
	4H	16,7	17,8	17,2	18,1	18,3	16,7	17,8	17,2	18,1	18,3
	6H	17,3	18,2	17,6	18,5	18,9	17,3	18,2	17,6	18,5	18,9
	8H	17,5	18,4	17,9	18,7	19,1	17,5	18,4	17,9	18,7	19,1
	12H	17,7	18,6	18,1	18,9	19,4	17,7	18,6	18,1	18,9	19,4
4H	2H	15,7	16,8	16,1	17,0	17,3	15,7	16,8	16,1	17,0	17,3
	3H	16,9	17,8	17,3	18,1	18,6	16,9	17,8	17,3	18,1	18,6
	4H	17,5	18,3	17,9	18,7	19,2	17,5	18,3	17,9	18,7	19,2
	6H	18,1	18,9	18,6	19,3	19,6	18,1	18,9	18,6	19,3	19,6
	8H	18,4	19,1	19,0	19,5	19,9	18,4	19,1	19,0	19,5	19,9
	12H	18,7	19,3	19,2	19,7	20,2	18,7	19,3	19,2	19,7	20,2
8H	4H	17,7	18,4	18,3	18,8	19,2	17,7	18,4	18,3	18,8	19,2
	6H	18,6	19,1	19,1	19,6	20,2	18,6	19,1	19,1	19,6	20,2
	8H	19,1	19,5	19,6	20,0	20,7	19,1	19,5	19,6	20,0	20,7
	12H	19,5	19,8	20,1	20,4	21,0	19,5	19,8	20,1	20,4	21,0
12H	4H	17,8	18,3	18,3	18,8	19,3	17,8	18,3	18,3	18,8	19,3
	6H	18,7	19,2	19,3	19,7	20,4	18,7	19,2	19,3	19,7	20,4
	8H	19,2	19,6	19,8	20,1	20,7	19,2	19,6	19,8	20,1	20,7
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,2					0,1 / -0,2				
S = 1.5H		0,4 / -0,5					0,4 / -0,5				
S = 2.0H		0,9 / -0,7					0,9 / -0,7				
CIE 117-1995. Corrected glare indices referring to 4058 lm total luminous flux											

### Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	106	106	106	101	101	101	99
1	110	106	102	98	107	103	100	97	99	96	94	95	93	90	91	89	88	86
2	101	94	88	83	99	92	87	82	88	84	80	85	81	78	82	79	76	74
3	94	84	77	71	91	83	76	70	80	74	69	77	72	68	74	70	67	65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	67	63	59	57
5	80	69	61	55	78	67	60	54	65	59	54	63	57	53	61	56	52	50
6	75	63	54	49	73	62	54	48	60	53	48	58	52	47	56	51	47	45
7	70	57	49	44	68	56	49	43	55	48	43	53	47	43	52	46	42	40
8	65	53	45	39	64	52	44	39	51	44	39	49	43	39	48	42	38	37
9	61	49	41	36	60	48	41	36	47	40	35	46	40	35	45	39	35	33
10	57	45	38	33	56	45	37	33	43	37	32	43	37	32	42	36	32	30

LAMPS (number of lamps)

### Luminaire budgetary diagram




### Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
{LUM0-10}	518 lm	781 lm	885 lm	678 lm	450 lm	275 lm	171 lm	73,7 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
7,99 lm	6,24 lm	6,21 lm	6,19 lm	5,88 lm	5,03 lm	3,98 lm	2,59 lm	0,845 lm

LCS table


BUG rating:	B2 U2 G1	
Forward light	Lumens	Lumens %
Low(0-30):	739,8	18,2%
Medium(30-60):	1006,5	24,8%
High(60-80):	223	5,5%
Very high(80-90):	36,9	0,9%
Back light		
Low(0-30):	739,8	18,2%
Medium(30-60):	1006,5	24,8%
High(60-80):	223	5,5%
Very high(80-90):	36,9	0,9%
Uplight		
Low(90-100):	8,2	0,2%
High(100-180):	36,9	0,9%

LCS graph





### Warmup curve



### Warmup result

Warmup time:	Lamp stabilized in 15 min 2 sec
Warmup variation	-0,3%

### Warmup conditions

Stable period:	15 min
Stable change max:	2,0%
Minimum time:	15 min

### Color temperature change

CCT start	CCT change	CCT end
2950 K	0 K	2950 K


### Output change

Output start	Output change	Output end
4067 lm	-10 lm	4058 lm


**Flicker curve (complete sampled flicker signal)**



**Flicker frame (frame of one flicker period)**



**Flicker FFT (frequency scope of flicker curve)**



**Flicker results:**

Flicker frequency:		n/a Hz	
Flicker index:	n/a	JA8/10 40Hz	n/a %
Flicker percentage:	n/a %	JA8/10 90Hz	n/a %
SVM: (Visual flicker)	n/a	JA8/10 200Hz	n/a %
PstLM	n/a	JA8/10 400Hz	n/a %
Mp	n/a	JA8/10 1000Hz	n/a %

**Flicker conditions:**

Sample rate:	n/a samples/second
--------------	--------------------